Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model Number: SUPDMB6KIEC

Detachable PDU option for compatible SmartOnline UPS Systems

Highlights

- Detachable PDU backplate with manual bypass switch serves as a replacement PDU for configured SU6000RT4UHVG UPS systems
- Can also be used to convert any high voltage UPS configuration using the SU6000RT4UHVPM power module to include C19 outlets
- 4 C19 output receptacles
- Hardwire input supported
- Attaches via unit-specific back panel electrical and bolt-on connections
- Manual bypass feature ensures maximum equipment availability

Description

The SUPDMB6KIEC UPS backplate with manual transfer switch serves as a replacement for the original backplate provided with SU6000RT4UHVG configurations. Can also be used to convert any high voltage UPS configuration using the SU6000RT4UHVPM power module to support hardwire input and 4 C19 output receptacles. Manual bypass feature ensures maximum availability of connected equipment while UPS maintenance occurs. Can accept input voltages of 200-240 VAC. Hardwire input / 4 C19 output connections.

System Requirements

- Requires SU6000RT4UHVPM UPS power module in any 200-240V AC configuration

Package Includes

- SUPDMB6KIEC detachable PDU

Features

Specifications

OVERVIEW	
Model Type	PDU Modules
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output nominal voltage	200, 208, 220, 230, 240 VAC
Overload protection	2 double pole 20A breakers protect 2 C19 outlets each

Outlet quantity / type	2 C19
INPUT	
Nominal Input Voltage(s) Supported	200V AC; 208V AC; 230V AC; 240V AC; 220V AC
Input connection type	Hardwire
Voltage compatibility (VAC)	200; 208; 220; 230; 240
PHYSICAL	
Shipping Dimensions (HWD/in)	6.9 x 20.1 x 10.8
Shipping Dimensions (HWD/cm)	17.5 x 51.1 x 27.4
Shipping weight (lbs)	7.7
Shipping weight (kg)	3.5
Unit Dimensions (HWD/in)	3.3 x 17.2 x 3.2
Unit Dimensions (HWD/cm)	8.4 x 43.7 x 8.1
Unit weight (lbs)	7.7
Unit weight (kg)	3.5
Material of construction	Sheet metal
SPECIAL FEATURES	
Appearance	All-black color scheme
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), CSA (Canada), CE (EU)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at http://www.tripplite.com/sku/SUPDMB6KIEC.

Copyright © 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.